SW-LR/ID-P

TOTAL WEIGHING SOLUTION™

Smart Weighing Scale


SW SERIES

SPECIFICATIONS

Model	SW-LR / ID-P						
Max.capacity	1/2kg	2.5/5kg	4/10kg	10/20kg	15/30kg		
Readability	0.5/1g	1/2g	2/5g	5/10g	5/10g		
Maximum tare	-0.9995	-2.499	-3.998	-9.995	-14.995		
Internal resolution	1/60,000						
External resolution	1/2,000 ~ 1/3,000						
Display digit	6 Digit						
Display type	LED						
Operating temperature	-10°C ~ 40°C						
Power	Rechargeable battery						
	12V DC adapter						
Battery life	SW-LR:10 / ID-P:30hrs after recharging the battery						
Platter size (mm)	SW-LR:230(W) x 190(D) ID-P:293(W) x 218(D)						
Dimensions (mm)	SW-LR:260(W)x287(D)x137(H) ID-P:320(W)x361(D)x444(H)						
Product weight	SW-LR:2.8kg ID-P:5.5kg						

SW-LR

DIMENSIONS



CAS



Lada sin costo **01 800 026 5331** ventas@akbasculas.com www.akbasculas.com j Atendemos en cualquier punto de la república !















Battery operation

SW-1W/1WR



1/2,000~1/3,000 dual interval resolution for better accuracy

• The SW-1W/1WR adopts dual interval technology, allowing for an automatic change of the SW-1W/1WR interval for an even more precise reading.


Rechargeable Battery operation (SW-1WR only)

• The SW-1WR can be used for up to 30 hours after charging the battery.

Unit:mm

141

DIMENSIONS



OPTIONS

- Rear display (Dual display)
- 9V DC adapter (SW-1W only)

Smart Weighing Scale

SW-1W/1WR

1/2kg 2.5/5kg 4/10kg 10/20kg 15/30kg

2/5g

-3.998

1/60,000

1/2,000 ~ 1/3,000

5 Digit (SW-1W), 6 Digit (SW-1WR)

LCD (SW-1W), LED (SW-1WR)

-10℃ ~ 40℃

Dry battery (D type x 6ea) or 9V DC adapter

9V DC adapter (SW-1W only)

Approx. 400hours or 800hours (Alkaline battery)

Approx. 30hours (SW-1WR)

247(W) x 195(D)

278(W) x 317(D) x 141(H)

3.7kg

Pb battery,12V DC adapter (SW-1WR only)

5/10g

5/10g

-9.995 -14.995

MO

1/2g

-0.9995 -2.499

0.5/1g

Dust & Waterproof digital scale (Level IP 66)

Clear and Highly legible LED display (SW-1WR only)

• The SW-1W/1WR can be protected

from water, dirt and other external

• SW-1WR Series has a 19mm LED

display and uses 6 highly legible digits.

SPECIFICATIONS

Model

Max.capacity

Readability

Maximum tare

Display digit

Display type

Power

Battery life

agents.

Platter size (mm)

Dimensions (mm) Product weight

Internal resolution

External resolution

Operating temperature

12V DC adapter (SW-1WR only)





SW-15/1C



1/2,000~1/3,000 dual interval resolution for better accuracy

• The SW-1S/1C adopts dual interval technology, allowing for an automatic change of the SW-1S/1C interval for an even more precise reading.




Accurate counting function (SW-1C only)

• The SW-1C has a simple counting and limit function for quality product management. It is great for use in manufacturing, parts shops, hardware stores etc.

DIMENSIONS SW-1 Unit:mm 37

287







Smart Weighing Scale

SPECIFICATIONS

				the set of				
Model	SW-1S/1C							
c.capacity	1/2kg	2.5/5kg	4/10kg	10/20kg	15/30kg			
dability	0.5/1g	1/2g	2/5g	5/10g	5/10g			
kimum tare	-0.9995	-2.499	-3.998	-9.995	-14.995			
rnal resolution	1/60,000							
ernal resolution	1/2,000 ~ 1/3,000							
olay digit	5 Digit							
olay type	LCD							
rating temperature	-10°C ~ 40°C							
/er	Dry battery (D type x 6ea) or 9V DC adapter							
	Pb battery							
any life	Approx. 400hours or							
ery life	800hours (Alkaline battery)							
ter size (mm)	230(W) x 190(D)							
ensions (mm)	260(W) x 287(D) x 137(H)							
duct weight	2.8kg							

88888.

Clear and Highly legible LCD display

• SW-1 Series has a 25mm large LED display and uses 6 highly legible digits.



Used anywhere with battery power

• SW Series is operated by an AC adapter or alkaline batteries. Its compact design is great for use anywhere.



OPTIONS

• Rear display (Dual display) • AC adapter (9V/300mA) • Stainless steel platter / Fish tray Dust protection cover



ish tray 🔺

